

## MATERIAL SAFETY DATA SHEET

UNIVERSAL STENCILING & MARKING SYSTEMS  
205 15TH AVENUE SOUTHEAST  
ST. PETERSBURG, FL 33701

PHONE NUMBER: (727) 894-3027

REVISION DATE: 04-02-08

PREPARED BY: D.C. WRIGHT

EMERGENCY PHONE NUMBER: CHEMTREC EMERGENCY CONTACT ONLY 1-800-424-9300

### SECTION I: PRODUCT IDENTIFICATION

PRODUCT NAME: UNIVERSAL TYPE "M" NO LEAD YELLOW STENCILING AND MARKING INK

HEALTH HAZARD  
MINIMAL ..... 0  
SLIGHT ..... 1  
MODERATE ... 2  
SERIOUS ..... 3  
SEVERE ..... 4

HEALTH (2)  
FLAMMABILITY (3)  
REACTIVITY (0)

DOT CLASSIFICATION: UN-1210 FLAMMABLE LIQUID

### SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT NAME	%	CAS #	TLV/IPEL
ISOPROPYL ALCOHOL	38	67-63-0	400.0 ppm ACGIH TWA 500.0 ppm ACGIH STEL 400.0 ppm OSHA TWA 500.0 ppm OSHA-STEEL 400.0 ppm CAL OSHA-TWA
N-PROPYL ALCOHOL	5	71-23-8	200.0 ppm ACGIH TWA 200.0 ppm OSHA-TWA 300.0 ppm ACGIH-STEEL 250.0 ppm OSHA-STEEL 200.0 ppm CAL OSHA-TWA
N-PROPYL ACETATE	3	109-60-4	TLV 200.0 ppm IPEL 250.0 ppm
YELLOW PIGMENT #14	5	5468-75-7	10mg/m3- ACGIH 5mg/m3 - OSHA
RESIN	9	Proprietary mix	15mg/m3 OSHA PEL
TiO2	16	13463-67-7	15mg/m3 OSHA-TWA 10mg/m3- ACGIH-TWA 10mg/m3- AEL
ETHYLENE GLYCOL MONOBUTYL ETHER	24	111-76-2	25.0 ppm ACGIH-TWA 50 ppm OSHA-TWA 75 ppm ACGIH-STEEL

### SECTION III: PHYSICAL DATA

BOILING POINT	Above 198 DEG. F.
VAPOR DENSITY	vs. AIR - HEAVIER
EVAPORATION RATE	vs. BUTYL ACETATE - SLOWER
% VOLATILE/VOL	70%
WEIGHT/GALLON	APPROX: 9 LBS/GAL

APPEARANCE & ODOR	YELLOW LIQUID WITH ALCOHOL ODOR
-------------------	---------------------------------

SECTION IV: FIRE & EXPLOSION HAZARD DATA	
FLASH POINT	APPROX. 60 DEG. F. ASTM D-3828-05
EXTINGUISHING MEDIA	USE CARBON DIOXIDE, DRY CHEMICAL OR FOAM
SPECIAL FIRE FIGHTING PROCEDURES	WATER SPRAY MAY SPREAD FIRE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTO IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. USE SELF CONTAINED BREATHING APPARATUS & FULL PROTECTIVE EQUIPMENT RECOMMENDED.
UNUSUAL FIRE & EXPLOSION HAZARDS	THIS PRODUCT IS FLAMMABLE AND WILL ENHANCE BURNING. BURNING OF THIS PRODUCT WILL PRODUCE TOXIC VAPORS/FUMES.

SECTION V: HEALTH HAZARD DATA	
PRIMARY ROUTES OF ENTRY	
INHALATION	IF USE CONDITIONS GENERATE VAPORS IN AREAS WHERE ADEQUATE VENTILATION IS NOT AVAILABLE, NIOSH APPROVED VAPOR RESPIRATOR SHOULD BE WORN.
SKIN CONTACT	SKIN CONTACT SHOULD BE PREVENTED THROUGH USE OF PROTECTIVE CLOTHING.
SKIN ABSORPTION	MAY BE ABSORBED IN HARMFUL AMOUNTS.
EYE CONTACT	CONTACT MAY CAUSE SEVERE IRRITATION.
INGESTION	ALL FOOD SHOULD BE KEPT IN SEPARATE AREAS FROM THOSE WHERE INK IS STORED OR USED. INGESTION CAN LEAD TO IRRITATION OF THE DIGESTIVE TRACT AND COULD EVEN BE FATAL IN EXTREME CASES.
TOXICITY INFORMATION	ANIMAL STUDIES HAVE SHOWN SOME LIVER AND REPRODUCTIVE ORGAN DAMAGES WITH LONG TERM EXPOSURE. AS TO HOW THIS AFFECTS THE INDUSTRIAL USE OF THESE INGREDIENTS IS UNCLEAR.

EFFECTS OF OVEREXPOSURE	<p>INHALATION OF VAPORS OR MIST MAY IRRITATE NOSE &amp; THROAT. INHALATION OF HIGH CONCENTRATIONS MAY CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. SYMPTOMS OF EARLY TO MODERATE CNS DEPRESSION INCLUDE GIDDINESS, DIZZINESS, CONFUSION, DRUNKEN BEHAVIOR, HEADACHE, NAUSEA, DIARRHEA, VOMITING, TIREDNESS AND DROWSINESS. IN EXTREME CASES, SYMPTOMS OF CNS DEPRESSION INCLUDE STUPOR, CONVULSIONS, UNCONSCIOUSNESS, COMA AND EVEN DEATH. SKIN CONTACT MAY CAUSE IRRITATION AND REDDENING. PROLONGED CONTACT MAY CAUSE SWELLING AND SKIN DAMAGE. THIS PRODUCT IS READILY ABSORBED THROUGH THE SKIN. FREQUENT OR WIDESPREAD CONTACT MAY ABSORB HARMFUL AMOUNTS. THIS MATERIAL MAY BE HARMFUL IF SWALLOWED. BASED ON LABORATORY TEST DATA, OVEREXPOSURE MAY CAUSE DAMAGE TO, DISORDERS OF, OR ADVERSELY AFFECT THE FOLLOWING SYSTEMS, FUNCTIONS OR ORGANS: BLOOD, BLOOD FORMING ORGANS, LIVER, REPRODUCTIVE SYSTEMS.</p>
-------------------------	---

### EMERGENCY AND FIRST AID PROCEDURES

INHALATION	REMOVE FROM EXPOSURE. RESTORE BREATHING IF REQUIRED. TAKE TO A PHYSICIAN FOR DEFINITIVE MEDICAL TREATMENT.
SPLASH (EYES)	FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS APART. TAKE TO A PHYSICIAN FOR DEFINITIVE MEDICAL TREATMENT.
SPLASH (SKIN)	WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. DESTROY CONTAMINATED SHOES. CONSULT A PHYSICIAN IF IRRITATION OCCURS.
INGESTION	CALL POISON CONTROL CENTER IMMEDIATELY. DO NOT INDUCE VOMITING UNLESS TOLD BY COMPETENT MEDICAL AUTHORITY.

### SECTION VI: REACTIVITY DATA

STABILITY	STABLE
INCOMPATIBILITY (MATERIALS TO AVOID)	ALKALI AGENTS AND STRONG OXIDIZING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS	WHEN INVOLVED IN A FIRE, BURNING ORGANIC PIGMENTS MAY EVOLVE NOXIOUS FUMES WHICH MAY INCLUDE CARBON MONOXIDE, NITROUS OXIDES, OR OTHER TOXIC COMPOUNDS DEPENDING ON THE PIGMENT TYPE.
CONDITIONS TO AVOID	HEAT, SPARKS AND OPEN FLAMES

### SECTION VII: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS AND CONTACT WITH SKIN. RECOVER AS MUCH FREE LIQUID AS POSSIBLE WITH NON-SPARKING TOOLS. REMOVE REMAINDER WITH INERT ABSORBENT.
---	--

WASTE DISPOSAL METHOD	DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. ALL MATERIAL INCLUDING CLEAN UP MATERIAL SHOULD BE PLACED IN A CONTAINER FOR PROPER DISPOSAL.
-----------------------	---

### SECTION VIII: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION	USE ONLY IN WELL VENTILATED AREA TO KEEP VAPOR CONCENTRATION BELOW PEL.
IF SPRAYED	USE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS IN THE PRESSURE DEMAND MODE OR A SUPPLIED AIR RESPIRATOR.
VENTILATION	USE ADEQUATE VENTILATION TO PREVENT HIGH CONCENTRATION OF VAPOR.
PROTECTIVE GLOVES	REQUIRED FOR PROLONGED OR REPEATED CONTACT
EYE PROTECTION	IF SPLASH HAZARD EXISTS, USE SAFETY EYEWEAR.
OTHER PROTECTIVE EQUIPMENT	USE PROTECTIVE GARMENT AS REQUIRED.

### SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING & AND STORING	KEEP CONTAINERS CLOSED. STORE IN COOL, WELL VENTILATED AREA. OBSERVE SAFE HANDLING & STORING METHODS FOR FLAMMABLES.
OTHER PRECAUTIONS	CONTAINERS SHOULD BE GROUNDED WHEN POURING. THIS INK HAS NOT BEEN EVALUATED BY THE UNITED STATES DEPARTMENT OF AGRICULTURE (USDA) FOR USE IN PACKAGING MATERIAL IN DIRECT/INDIRECT CONTACT WITH FOOD PRODUCTS.
DOT HAZARD CLASSIFICATION	FLAMMABLE LIQUID UN1210
DOT LABELS REQUIRED	YES, FLAMMABLE LIQUID

### SECTION X: OTHER REGULATORY INFORMATION

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:  
 GLYCOL ETHERS: 24%

**\*\*\* DISCLAIMER \*\*\***

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS, TO THE BEST OF OUR UNIVERSAL STENCILING & MARKING SYSTEMS'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.