

Safety Data Sheet

Issue Date: 03-Feb-2021

Revision Date: 03-Feb-2021

Version 1

1. IDENTIFICATION

Product identifier

Product Name Type D Dark Blue

Other means of identification

SDS # USM-013
Product Code IU-DD44, IU-DD4QT, IU-DD4QTH, IU-DD4GL
UN/ID No UN1210

Recommended use of the chemical and restrictions on use

Recommended Use Printing ink.

Details of the supplier of the safety data sheet

Manufacturer Address

Universal Stenciling & Marking Systems, Inc.
205 15th Avenue S.E.
St. Petersburg, FL 33701
PH: 727-894-3027

Emergency telephone number

Emergency Telephone INFOTRAC: 1-800-535-5053

2. HAZARDS IDENTIFICATION

Appearance Dark blue liquid

Physical state Liquid

Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Flammable liquids	Category 3

Signal Word

Danger

Hazard statements

Harmful if swallowed
Harmful if inhaled
Causes skin irritation
Causes serious eye damage
Suspected of causing cancer
Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof equipment

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a poison center or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 If skin irritation occurs: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Ethylene Glycol Monobutyl Ether	111-76-2	30-33
Ethanol	64-17-5	18-23
n-Propyl Alcohol	71-23-8	9-12
n-Propyl acetate	109-60-4	2-4
Cellulose nitrate	9004-70-0	1-4
Methylisobutyl ketone	108-10-1	0.1-1
Solvent naphtha (petroleum), light aliphatic	64742-89-8	<1
Heptane	142-82-5	<1
Butyl acetate	123-86-4	<1
Toluene	108-88-3	Trace
Acetaldehyde	75-07-0	Trace

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice
Eye Contact

If exposed or concerned: Get medical advice/attention.
 Rinse cautiously with water for several minutes. Remove contact lenses, if present and

	easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
Skin Contact	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Ingestion	Call a poison center or doctor/physician if you feel unwell. Rinse mouth.

Most important symptoms and effects, both acute and delayed

Symptoms	May be harmful in contact with skin. Harmful if swallowed. Harmful if inhaled. Causes skin irritation. Causes serious eye damage. Suspected of causing cancer.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use CO2, dry chemical, or foam for extinction.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Use explosion proof equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Store locked up. Store in a well-ventilated place. Keep cool.

Incompatible Materials

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
n-Propyl Alcohol 71-23-8	TWA: 100 ppm	TWA: 200 ppm TWA: 500 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 500 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 625 mg/m ³	IDLH: 800 ppm TWA: 200 ppm TWA: 500 mg/m ³ STEL: 250 ppm STEL: 625 mg/m ³
n-Propyl acetate 109-60-4	STEL: 150 ppm TWA: 100 ppm	TWA: 200 ppm TWA: 840 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 840 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 1050 mg/m ³	IDLH: 1700 ppm TWA: 200 ppm TWA: 840 mg/m ³ STEL: 250 ppm STEL: 1050 mg/m ³
Methylisobutyl ketone 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³
Butyl acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH

Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Acetaldehyde 75-07-0	Ceiling: 25 ppm	TWA: 200 ppm TWA: 360 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 180 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 270 mg/m ³	IDLH: 2000 ppm

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Not determined
Appearance	Dark blue liquid	Odor Threshold	Not determined
Color	Dark blue		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting point / freezing point	Not determined	
Boiling point / boiling range	Not determined	
Flash point	27.5 °C / 81.5 °F	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Liquid-Not applicable	
Flammability Limit in Air		
Upper flammability or explosive limits	Not determined	
Lower flammability or explosive limits	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Relative Density	Not determined	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Not determined	
Decomposition temperature	Not determined	
Kinematic viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information****Eye Contact** Avoid contact with eyes.**Skin Contact** May be harmful in contact with skin.**Inhalation** Harmful if inhaled.**Ingestion** Harmful if swallowed.**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene Glycol Monobutyl Ether 111-76-2	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 486 ppm (Rat) 4 h = 450 ppm (Rat) 4 h
Ethanol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
n-Propyl Alcohol 71-23-8	= 1870 mg/kg (Rat)	= 4049 mg/kg (Rabbit)	> 13548 ppm (Rat) 4 h
Cellulose nitrate 9004-70-0	> 5 g/kg (Rat)	-	-
n-Propyl acetate 109-60-4	= 8700 mg/kg (Rat)	> 17756 mg/kg (Rabbit)	-
Methylisobutyl ketone 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h
Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
Solvent naphtha (petroleum), light aliphatic 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
Acetaldehyde 75-07-0	= 660 mg/kg (Rat)	= 3540 mg/kg (Rabbit)	= 13000 ppm (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Carcinogenicity Suspected of causing cancer. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Nitrate or nitrite ingested under conditions that result in endogenous nitrosation are considered IARC group 2A carcinogens. Group 3 IARC components are "not classifiable as human carcinogens".

Chemical name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Monobutyl Ether 111-76-2	A3	Group 3		
Ethanol 64-17-5	A3	Group 1	Known	X
Cellulose nitrate 9004-70-0		Group 2A		X
Methylisobutyl ketone 108-10-1	A3	Group 2B		X
Acetaldehyde 75-07-0	A2	Group 1 Group 2B	Reasonably Anticipated	X
Toluene 108-88-3		Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Oral LD50 1,225.10 mg/kg

Dermal LD50 2,983.10 mg/kg

ATEmix (inhalation-dust/mist) 4.38 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ethylene Glycol Monobutyl Ether 111-76-2		2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static	1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50
Chemical name	Algae/aquatic plants	Fish	Crustacea

Ethanol 64-17-5		13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static	10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static 9268 - 14221: 48 h Daphnia magna mg/L LC50
n-Propyl Alcohol 71-23-8		4480: 96 h Pimephales promelas mg/L LC50 flow-through	3642: 48 h Daphnia magna mg/L EC50 3339 - 3977: 48 h Daphnia magna mg/L EC50 Static
n-Propyl acetate 109-60-4		56 - 64: 96 h Pimephales promelas mg/L LC50 static 56 - 64: 96 h Pimephales promelas mg/L LC50 flow-through	318: 24 h Daphnia magna mg/L EC50
Methylisobutyl ketone 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
Butyl acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L EC50
Solvent naphtha (petroleum), light aliphatic 64742-89-8	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50		
Acetaldehyde 75-07-0	237 - 249: 120 h Nitzschia linearis mg/L EC50	28.0 - 34.0: 96 h Pimephales promelas mg/L LC50 flow-through 39.8 - 46.8: 96 h Pimephales promelas mg/L LC50 static 53: 96 h Lepomis macrochirus mg/L LC50 static 1.8 - 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static	3.64 - 6.15: 48 h Daphnia magna mg/L EC50 Static 48.3: 48 h Daphnia magna mg/L EC50
Toluene 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	12.6: 96 h Pimephales promelas mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static	11.5: 48 h Daphnia magna mg/L EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Ethylene Glycol Monobutyl Ether 111-76-2	0.81
Ethanol 64-17-5	-0.32
n-Propyl Alcohol 71-23-8	0.34
Methylisobutyl ketone 108-10-1	1.19
Chemical name	Partition coefficient

Heptane 142-82-5	4.66
Butyl acetate 123-86-4	1.81
Toluene 108-88-3	2.7
Acetaldehyde 75-07-0	0.5

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methylisobutyl ketone 108-10-1		Included in waste stream: F039		U161
Acetaldehyde 75-07-0				U001
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Ethanol 64-17-5	Toxic Ignitable
n-Propyl Alcohol 71-23-8	Toxic Ignitable
n-Propyl acetate 109-60-4	Toxic Ignitable
Chemical name	California Hazardous Waste Status

Cellulose nitrate 9004-70-0	Ignitable in ether and alcohol Reactive in ether and alcohol
Heptane 142-82-5	Toxic Ignitable
Butyl acetate 123-86-4	Toxic
Toluene 108-88-3	Toxic Ignitable
Acetaldehyde 75-07-0	Toxic Ignitable

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1210
 Proper Shipping Name Printing ink
 Hazard class 3
 Packing Group III

IATA

UN number UN1210
 Proper Shipping Name Printing ink
 Transport hazard class(es) 3
 Packing Group III

IMDG

UN number UN1210
 Proper Shipping Name Printing ink
 Transport hazard class(es) 3
 Packing Group III

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethylene Glycol Monobutyl Ether	X	ACTIVE	X	X	X	X	X	X	X
Ethanol	X	ACTIVE	X	X	X	X	X	X	X
n-Propyl Alcohol	X	ACTIVE	X	X	X	X	X	X	X
Cellulose nitrate	X	ACTIVE	X		X	X	X	X	X
n-Propyl acetate	X	ACTIVE	X	X	X	X	X	X	X
Methylisobutyl ketone	X	ACTIVE	X	X	X	X	X	X	X
Butyl acetate	X	ACTIVE	X	X	X	X	X	X	X
Heptane	X	ACTIVE	X	X	X	X	X	X	X
Solvent naphtha (petroleum), light aliphatic	X	ACTIVE	X	X		X	X	X	X
Acetaldehyde	X	ACTIVE	X	X	X	X	X	X	X
Toluene	X	ACTIVE	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methylisobutyl ketone 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Acetaldehyde 75-07-0	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Toluene 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

SARA 313

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol Monobutyl Ether - 111-76-2	111-76-2	30-33	1.0
Methylisobutyl ketone - 108-10-1	108-10-1	0.1-1	1.0
Acetaldehyde - 75-07-0	75-07-0	Trace	0.1
Toluene - 108-88-3	108-88-3	Trace	1.0

CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl acetate	5000 lb			X
Toluene	1000 lb	X	X	X
Acetaldehyde	1000 lb			X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Ethanol - 64-17-5	Carcinogen Developmental
Methylisobutyl ketone - 108-10-1	Carcinogen Developmental
Toluene - 108-88-3	Developmental
Acetaldehyde - 75-07-0	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethylene Glycol Monobutyl Ether 111-76-2	X	X	X
Ethanol 64-17-5	X	X	X
n-Propyl Alcohol 71-23-8	X	X	X
n-Propyl acetate 109-60-4	X	X	X
Cellulose nitrate 9004-70-0	X	X	X
Methylisobutyl ketone 108-10-1	X	X	X
Butyl acetate 123-86-4	X	X	X
Heptane 142-82-5	X	X	X
Acetaldehyde 75-07-0	X	X	X
Toluene 108-88-3	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards**

Not determined

Flammability

Not determined

Instability

Not determined

Special Hazards

Not determined

HMIS**Health Hazards**

Not determined

Flammability

Not determined

Physical hazards

Not determined

Personal Protection

Not determined

Issue Date: 03-Feb-2021

Revision Date: 03-Feb-2021

Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet